



570 HANCE RD.  
BINGHAMTON, NY 13903  
TEL. (607) 669-4822 FAX (607) 669-4595  
<http://www.accessunlimited.com>

## **Easy-Reach Generation 7.0/7.5 Specifications**

**WEIGHT CAPACITY:** 275 lbs./125 kgs. (up to 360 lb/165 kg capacity available on certain models)

**UNIT WEIGHT:** Varies from application to application, average is 140 lb/65 kg

**LIFTING HEIGHT:** Varies greatly from application to application. Average 17"/430mm (Longer travels available upon request)

**APPLICATION ENGINEERING:** Each model of the Generation 7.0 is custom-built for the make and model of the particular vehicle. Most Generation 7.5 lifts are also custom-built for the make and model.

**PAINT:** Charcoal hammered finish

**LIMIT SWITCHES:** Magnetic proximity sensors (no mechanical limit switches)

**FACTORY SEAT SLIDE TRACKS & POWER FUNCTIONS:** Maintained in nearly all applications. Contact your AU rep for details on a particular application.

**CONTROL CIRCUITRY:** Programmable logic controller with full onboard LED diagnostics

**INTERLOCK:** Seat will not operate with door closed and alarm sounds when door closed if seat not in fully latched position

**VEHICLE STRUCTURAL DRILLING & MODIFICATION:** Not necessary for most applications

**MANUAL BACKUP SYSTEMS:** Manual crank provided for both rotate motor release and up/down actuator

**ROTATE MOTOR:** 12V electric gearmotor

**UP/DOWN ACTUATOR/MOTOR:** 12V electric recirculating ballscrew

**SEAT:** Factory seat utilized in all applications

**DOOR & TRIM PANEL MODIFICATIONS:** Required on some models. When needed, door panel kit is supplied. No door panel mod required when using Slimline version of Easy-Reach Generation 7.0 or 7.5

**AIRBAG:** Seat airbag and sensors remain fully functional

**SEAT BELTS:** Factory seatbelts are retained.

**SHIPPING:** Ships via truck

**POWER:** 12V DC, separate installed wiring, powered by car battery with supplied circuit breaker